

Which table is right for you?

Surgical C-Arm Table 840



Surgical C-Arm Table 846



Pain Management C-Arm Table 870



Urology C-Arm Table 800



Brachytherapy C-Arm Table 810



3D Imaging C-Arm Table 820



- 058-840 Table, Surgical C-Arm, Contour, 115 VAC
- 058-840-10 Table, Surgical C-Arm, Rectangle, 115 VAC
- 058-845 Table, Surgical C-Arm, Contour, 230 VAC
- 058-845-10 Table, Surgical C-Arm, Rectangle, 230 VAC

- 058-846 Table, Surgical C-Arm, Contour, 115 VAC
- 058-846-10 Table, Surgical C-Arm, Rectangle, 115 VAC
- 058-847 Table, Surgical C-Arm, Contour, 230 VAC
- 058-847-10 Table, Surgical C-Arm, Rectangle, 230 VAC

- 058-870 Table, Surgical C-Arm, Contour, 115 VAC
- 058-870-10 Table, Surgical C-Arm, Rectangle, 115 VAC
- 058-875 Table, Surgical C-Arm, Contour, 230 VAC
- 058-875-10 Table, Surgical C-Arm, Rectangle, 230 VAC

- 058-800 Table, Urology C-Arm, 800, 115 VAC
- 058-805 Table, Urology C-Arm, 800, 230 VAC

- 058-810 Table, Brachytherapy, 810, 115 VAC
- 058-815 Table, Brachytherapy, 810, 230 VAC

- 058-820 Table, 3D Imaging C-Arm, 115 VAC
- 058-825 Table, 3D Imaging C-Arm, 230 VAC

Shared Specifications:

Dimensions:
Overall: 97" l x 26" w (246 x 66 cm) with OR accessory rails

Tabletop: 97" l x 24" w (246 x 61 cm) – choice of classic contoured or rectangular design

Radiolucent Area: 75" l x 24" w (191 x 61 cm)

Tabletop Material: Carbon fiber with integral head section

Mattress: Seamless, 2" thick (5 cm)

Attenuation: 1.2 mm Aluminum equivalence

Patient Restraints: Three body straps

Finish: Stainless Steel

Patient Capacity: 500 lb (227 kg)

Warranty: Three years parts and labor

Certifications: ANSI/AAMI ES60601-1:2005 +C1 (2009) +A1 (2012) +A2 (2010); CAN/CSA C22.2 No. 60601-1:14; CAN/CSA-C22.2 NO. 60601-2-46:12; IEC 60601-1-2-46:2016.

CDRH registered and FDA Device Listed



840

846

870

Motions:	840	846	870
Height Adjustable: 33.5" to 43.5" (84 to 109 cm)	—	Height Adjustable: 32" to 42" (81 to 106 cm)	—
Tabletop X Motion (head-to-toe float): 35" (88.9 cm)	—	Tabletop X Motion (head-to-toe float): 35" (89 cm)	—
Tabletop Y Motion (side-to-side float): 10" (25.4 cm)	—	Tabletop Y Motion (side-to-side float): 10" (25.4 cm)	—
Trendelenburg: 0° to 20°	—	—	Trendelenburg: 0° to 20°
Reverse Trendelenburg: 0° to 20°	—	—	Reverse Trendelenburg: 0° to 20°
Isocentric Lateral Roll: 0° to ±15°	—	—	Isocentric Lateral Roll: 0° to ±15°

Controls:	840	846	870
Hand Control: Activates height, isocentric lateral roll and Trendelenburg motions	—	Hand Control: Activates height	Hand Control: Activates height, isocentric lateral roll and Trendelenburg motions
Foot Control: Activates all motions (has release for float)	—	—	Foot Control: Activates all motions
Mushroom-Top Control: Releases X-Y Tabletop motions	—	Mushroom-Top Control: Releases X-Y Tabletop motions	—

Accessory Rails:	840	846	870
Standard OR accessory rails 49.5" x 1.12" x .375" (124 x 2.86 x .95 cm) mounted near foot end of table	—	Standard OR accessory rails 49.5" x 1.12" x .375" (124 x 2.86 x .95 cm) mounted near foot end of table	—
Weight: 641 lb (291 kg)	—	—	—
Shipping Weight: 865 lb (392 kg)	—	Shipping Weight: 800 lb (363 kg)	Shipping Weight: 749 lb (340 kg)
Power: 115 VAC or 230 VAC and battery. Battery automatically charges when table is plugged in. An optional battery with separate charging unit provides continuous, cordless operation.	—	Power: 115 VAC or 230 VAC	Power: 115 VAC or 230 VAC

Catheter Tray Extension (removable):	840	846	870
18" l x 24" w (45.7 x 61 cm) non-radiolucent	—	Optional	Optional

Shared Specifications:

Motions:
Tabletop Y Motion (side-to-side): 10" (25.4 cm)

Trendelenburg: 0° to 20°

Reverse Trendelenburg: 0° to 20°

Lateral Roll: 0° to 20°

Controls:
Hand Control: Activates all motions

Foot Control: Activates all motions

Accessory Rails: Standard OR accessory rails, 1.125" x .375" (2.86 x .95 cm).

Power: 115 VAC or 230 VAC and Battery. Battery automatically charges when table is plugged in. An additional battery can be charged with optional wall-mounted charger.

Warranty: Three years parts and labor

Certifications: ANSI/AAMI ES60601-1:2005 +C1 (2009) +A1 (2012) +A2 (2010); CAN/CSA C22.2 No. 60601-1:14; CAN/CSA-C22.2 NO. 60601-2-46:12; IEC 60601-1-2-46:2016.

CDRH registered and FDA Device Listed



800 and 810

820

Dimensions:	800 and 810	820
Dimensions: 84.5" l x 25.5" w (214.6 x 64.8 cm) with OR accessory rails	—	Dimensions: 103.75" l x 26" w (264 x 66 cm) with OR accessory rails
Tabletop: 53" l x 21" w (134.6 x 53.3 cm); 84" l (213.4 cm) with extension	—	Tabletop: 103.75" l x 24" w (264 x 61 cm) includes head and leg extension
Lightweight Extension (for patient transfer only, not for imaging): 26.5" l x 21" w (67.3 x 53.3 cm)	—	—
—	—	Radiolucent Area: 3D Imaging Area: 22.5" l x 24" w (57.1 x 61 cm)
Radiolucent Extension: 31" l x 25.5" w (78.7 x 64.8 cm) with OR accessory rails	—	Radiolucent Extension (Fibersin™, non-3D): 29" l x 22.5" w (73.6 x 57.1 cm)
Radiolucent Area: 54" l x 17.5" w (137.2 x 44.5 cm)	—	Total Radiolucent Area (Combined): 51.5" l x 24" w (131 x 61 cm)
—	—	Head-End Extension (non viewable): 18.2" l x 24" w (46 x 51 cm)
Tabletop Material: Three Fibersin™ sections – each with individual 2" mattress	—	Tabletop Material: Carbon fiber
Mattress: Individual, seamless, 2" thick (5 cm), one for each section	—	Mattress: Vinyl covered, seamless, 2" thick (5 cm)

Motions:	800 and 810	820
Height Adjustable: 34" to 43.5" (86.4 to 110.5 cm)	—	Motions: Height Adjustable: 34" h to 44" h (86 to 112 cm)
Tabletop X Motion (head-to-toe): 20" (51 cm)	—	Tabletop X Motion (head-to-toe): 20" (51 cm)
Fowler Positioning: Adjusts from 0° to 80° with touch handle lock/unlock	—	—

Optional:	800 and 810	820
X-Ray Film Tray: Removable film cassette tray for 14" x 17" film with cassette mask for 10" x 12" film. Film cassette tray can be removed from either side of the table.	—	—
X-Ray Grid: Removable X-Ray grid, 103 line, 8:1 ratio	—	—
—	—	Head-End: 30" l (75 cm)
—	—	Foot-End: 7.75" l (20 cm)
Patient Restraints: Two body straps, two ankle straps	—	—
Finish: Powder coat	—	—
Patient Capacity: In urologic position: 500 lb (227 kg) In use with radiolucent extension: 400 lb (181.4 kg) Weight tested to four times the patient load rating	—	Patient Capacity: 500 lb (227 kg); weight tested to four times the patient load rating.
—	—	Weight: 542 lb (246 kg)
Shipping Weight 800: 903 lb (409.6 kg)	—	Shipping Weight: 700 lb (318.1 kg)
Shipping Weight 810: 877 lb (398.6 kg)	—	—