



Clear-Lead™ Mobile Barriers

Sleek Design for Superior Infection Control

FEATURES

- Meets all infection control criteria
- Sleek design is easy to clean
- Durable and shatter-resistant protection
- Effortless maneuverability
- 0.5 mm lead equivalency window
- 0.8 mm lead opaque panel
- Superior stability



DESCRIPTION

Clear-Lead acrylic mobile X-ray barriers are designed for use around any imaging procedures using ionizing radiation, e.g., fluoroscopy, X-ray, CT and mammography.

Grab-handle edges and large casters make them effortless to maneuver. Clear-Lead Mobile Barriers offer large, durable and shatter-resistant protection wherever it's needed.

Easy-to-Sanitize Surfaces

The greatest advantage of these barriers over others on the market is the sleek design. With no exposed hardware and a solid exterior, harmful bacteria has no place to hide and thrive. Plus, the opaque section of the shield is covered with plastic laminate resulting in a smooth, easy-to-clean surface – and more effective infection control.

CLEAR-LEAD MOBILE BARRIERS



Clear-Lead Barrier Standard Window 042-580.



Clear-Lead Barrier Full Window 042-582.

SPECIFICATIONS

042-580 Clear-Lead Mobile Barrier, Standard Window:

Dimensions:

- Overall: 33" w x 73.62" h (84 x 187 cm)
- Window: 30" w x 22" h (76 x 56 cm)
- Opaque Panel: 30" w x 46.25" h (76 x 117 cm)
- Shielding Area: 30" w x 68.25" h (76 x 173 cm)

Shielding:

- Window: 0.5 mm lead equivalency
- Opaque Panel: 0.8 mm lead

- Leg Depth: 10.5" (26.7 cm)
- Casters: Four hospital grade; two locking, two non-locking

- Weight: 103 lb (47 kg)
- Warranty: One year parts and labor

042-582 Clear-Lead Mobile Barrier, Full Window:

Dimensions:

- Overall Dimensions: 33" w x 73.62" h (84 x 187 cm)
- Window: 30" w x 46" h (76 x 116.8 cm)
- Opaque Panel: 30" w x 22.25" h (76 x 56.5 cm)
- Shielding Area: 30" w x 68.25" h (76 x 173 cm)

Shielding:

- Window: 0.5 mm lead equivalency
- Opaque Panel: 0.8 mm lead

- Leg Depth: 10.5" (26.7 cm)
- Casters: Four hospital grade; two locking, two non-locking

- Weight: 97 lb (44 kg)
- Warranty: One year parts and labor

ORDERING INFORMATION

042-580	Barrier, Clear-Lead, Standard Window Window size 30" w x 22" h (76 x 56 cm)
042-582	Barrier, Clear-Lead, Full Window Window size 30" w x 46" h (76 x 116.8 cm)

